

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

Health monitoring

Patent Number: ☐ US5749365
Publication date: 1998-05-12
Inventor(s): MAGILL ALAN (GB)
Applicant(s):
Requested Patent: ☐ WO9308734
Application Number: US19940232147 19940505
Priority Number(s): GB19910023638 199111107; WO1992GB02064 19921109
IPC Classification: A61B5/04
EC Classification: A61B5/00B4, A61B5/0205, A61B5/113B
Equivalents: CA2123126, ☐ EP0611288 (WO9308734), JP7500748T

Abstract

PCT No. PCT/GB92/02064 Sec. 371 Date May 5, 1994 Sec. 102(e) Date May 5, 1994 PCT Filed Nov. 9, 1992 PCT Pub. No. WO93/08734 PCT Pub. Date May 13, 1993A method for monitoring vital signs of a human or animal subject includes clothing the subject in an elastically deformable shirt or undershirt, removably attaching a carrier carrying a sensor to the shirt or undershirt, adjacent the thoracic and abdominal regions of the subject, sensing elastic deformations of the shirt or undershirt corresponding to one or more of the group of vital signs including respiration, heart function, heart rhythm, generating electrical signals representative of the deformations, and transmitting the signals to a remote receiver for processing.

Data supplied from the esp@cenet database - 12




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : A61B 5/113, 5/00	A1	(11) International Publication Number: WO 93/08734 (43) International Publication Date: 13 May 1993 (13.05.93)
(21) International Application Number: PCT/GB92/02064 (22) International Filing Date: 9 November 1992 (09.11.92) (30) Priority data: 9123638.0 7 November 1991 (07.11.91) GB (71)(72) Applicant and Inventor: MAGILL, Alan, Remy [GB/GB]; 1 Russel Chambers, Covent Garden, London WC2E 8AA (GB). (74) Agent: COLES, Graham, Frederick; Graham Coles & Co, 24 Seeleys Road, Beaconsfield, Buckinghamshire HP9 1SZ (GB). (81) Designated States: CA, JP, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, SE).		Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>

(54) Title: HEALTH MONITORING**(57) Abstract**

Physiological monitoring of a baby is carried out from a fabric patch (2) that is attached by fibre hook-and-eye fastening to the baby's conventional, stretchable vest (1). The laminated patch (2), which bridges the baby's thoracic and abdominal regions, includes a concealed substrate (4) that carries piezo-electric film strips (10, 11) which sense, in those regions respectively, elastic deflections of the vest (1) caused by the baby's respiratory and heart functions. Signals from the strips (10, 11), together with a body-temperature signal from a thermistor (17, Figure 4), are processed and transmitted via an inductive-loop antenna (19) of the patch (2), to a remote unit (21, Figure 5) for further, more detailed processing to derive representation *inter alia* of thoracic-abdominal synchrony/asynchrony. The result is stored and monitored against stored clinical-data for display and alarm operation; the stored data is accessed by a data logger (31, Figure 5) for detailed analysis. Patch-attachment can be under a flap (43, Figure 6) bridging an opening (44) in the vest (41), or may be internally, rather than externally, of the vest.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NL	Netherlands
BE	Belgium	GN	Guinea	NO	Norway
BF	Burkina Faso	GR	Greece	NZ	New Zealand
BG	Bulgaria	HU	Hungary	PL	Poland
BJ	Benin	IE	Ireland	PT	Portugal
BR	Brazil	IT	Italy	RO	Romania
CA	Canada	JP	Japan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SK	Slovak Republic
CI	Côte d'Ivoire	LJ	Liechtenstein	SN	Senegal
CM	Cameroon	LK	Sri Lanka	SU	Soviet Union
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	MC	Monaco	TG	Togo
DE	Germany	MG	Madagascar	UA	Ukraine
DK	Denmark	ML	Mali	US	United States of America
ES	Spain	MN	Mongolia	VN	Viet Nam
FI	Finland				

Health Monitoring

The present invention relates to health monitoring, and is especially concerned with monitoring one or more vital signs of a human or animal subject.

Facilities for monitoring vital signs (embracing respiration, pulse, body temperature and blood pressure) of a subject are readily available in the context of a hospital or clinic. Whereas such facilities can, as a general matter, also be used and adapted for monitoring a subject out of that context, for example in the home environment, the equipment involved is normally not only expensive, but also obtrusive, cumbersome and inconvenient to an extent that its use is unacceptable or creates an undesirable intrusion into everyday life.

It is one of the objects of the present invention to facilitate the monitoring of vital signs in a less obtrusive, cumbersome and inconvenient manner than with known equipment.

According to one aspect of the present invention there is provided a method for monitoring vital signs of a human or animal subject, wherein the subject wears a vest in the form of a garment that has stretch both laterally and longitudinally of the subject's body to fit the body closely, elastic deflections of the vest related to respiratory and/or heart functions of the subject are sensed in both the thoracic and abdominal regions of the subject by sensors that are carried by a common carrier attached to the vest, and signals dependent on the sensed deflections are transmitted for reception and analysis remotely of the subject.

35

According to another aspect of the invention a system for monitoring vital signs of a human or animal subject,

comprises a vest for wear by the subject in the form of a garment that has stretch both laterally and longitudinally of the subject's body to fit the body closely, sensors that are carried by a common carrier
5 attached to the vest for sensing in both the thoracic and abdominal regions of the subject elastic deflections of the vest related to the subject's respiratory and/or heart functions, and means for transmitting signals dependent on the sensed deflections for reception and
10 analysis remotely of the subject.

The method and system of the invention are of especial advantage where monitoring is to be carried out in circumstances, which may occur in the environment of a
15 hospital or clinic, but may be more significant in the home environment, where the presence and use of conventional health monitoring equipment is likely to cause distraction and anxiety for the subject concerned, and, possibly also, for those involved with the subject.
20 For example, with apnoea-monitoring of a baby in its home environment, there is a risk that the visible presence of monitoring equipment will have an adverse effect on the welfare of both the infant and its parents.

25 With the method and system of the present invention there is the advantage that monitoring can be carried out in an unobtrusive manner, and the vest worn can be of a conventional, everyday form that can be laundered in the usual way. More particularly, the use of a common
30 carrier attached to the vest and carrying the sensors for sensing the elastic deflections, facilitates concealment of the sensors. In this respect moreover, the carrier may have an external decorative form which not only hides the sensors but diverts attention from its principal
35 purpose. There is, accordingly, the advantage that monitoring can be carried out against the background of normal, everyday life without the intrusion of unusual

and cumbersome objects that might give cause for apprehension or concern to the subject and/or for the subject's welfare.

- 5 There is particular advantage where all cable or other connections to the baby or other subject are eliminated by using electromagnetic-wave transmission of signals from the vest to the remote, monitoring location. The means for such transmission may also be carried by, and
10 concealed with the sensors within, the common carrier.

- The common carrier, which may be attached to the inside or outside of the vest, is preferably provided in the form of a patch that is releasably attached to the vest;
15 this facilitates change of vest and laundering, and replacement of the patch in the event of malfunction. Releasable attachment may be achieved by use of fabric fastening (for example, fastening of the kind sold under the Registered Trade Mark VELCRO) based on the inter-
20 engagement of hook fibres with other fibres, or by use of press-stud, laced or button attachment.

- Where press-stud, laced or button attachment is used, the appropriate location for securing the patch to the vest
25 will require no further definition, but where other attachment is used, the relevant location can be defined by marking included with the vest. However, by suitably dimensioning, configuring or otherwise defining the patch, it may be possible to avoid the necessity for any
30 definition of location on the vest itself, and in any event, for most situations the precise location of the sensors on the body will not be critical. The fact that the sensors are carried as one by the carrier, maintains their relative positions and enables their appropriate
35 placement relative to the subject's body to be executed in a simple and convenient, single operation.

As an alternative, the patch may be accommodated under a flap or within a pocket of the vest, so that its location on the vest is clearly established. But the use of a flap or pocket also has the benefit of at least partially
5 concealing the patch and limiting the possibility of it being inadvertently detached by the subject.

Where fabric fastening based on fibre hook-and-eye interengagement is used for attaching the patch to the
10 vest, and, possibly, also for holding a covering flap or pocket closed upon it, the structure of the vest may be such that it naturally provides the necessary 'eye' fibres for engagement by the hooks in the fastening, or can be fluffed up to do so where appropriate. The vest
15 in this regard may be of cotton and preferably of a seamless, knitted form so as to have good contour-conforming, stretch qualities.

The elastic deflections of the vest may be sensed by
20 strain gauges that involve piezo-electric film and are arranged to respond, for example, to the extension and contraction of the vest in the thoracic and abdominal regions respectively, in accordance with the subject's breathing pattern and heart hydraulics. The signals
25 provided by these, or by other sensors responsive to the elastic deflections, may be processed, for example using adaptive filtering techniques, to provide representations of thoracic-abdominal motion suitable for the detection of loss of abdominal-thoracic synchrony. At least part
30 of the processing may be carried out by an electrical circuit carried by the common carrier attached to the vest.

The common carrier, whether in the form of a patch
35 releasably attached to the vest or otherwise, may be of a laminated construction that includes a printed-circuit substrate on which the sensors are mounted. Means, for

example in the form of a thermistor, may be included for sensing the subject's body temperature. When the carrier is attached to the outside of the vest, a small hole may be provided in the vest to enable the thermistor or other temperature-sensing means to project through to make contact with the subject's skin, or to have unobstructed exposure to the skin, but it is generally adequate for sensing to be made via the vest without special adaptation.

Methods and systems for monitoring vital signs of a human subject in accordance with the present invention, will now be described, by way of example, with reference to the accompanying drawings in which:

Figure 1 is view of a baby wearing a vest forming part of a first health-monitoring system in accordance with the present invention;

Figures 2 and 3 illustrate the laminate construction of a carrier patch that is worn on the vest of Figure 1 and incorporates an electrical circuit for use in monitoring the health of the baby, Figure 2 being an exploded view showing the laminate split apart layer from layer, and Figure 3 showing a cross-section of part of the patch to an enlarged scale;

Figure 4 is a block schematic diagram of the electrical circuit incorporated in the patch of Figures 2 and 3;

Figure 5 is a block schematic diagram of the electrical circuit of a remote unit used in conjunction with the vest and its patch in monitoring the health of the baby of Figure 1; and

Figure 6 shows a second system for the health-monitoring of a baby, in accordance with the present invention, with

a carrier patch of the system removed from a flap-pocket of the vest.

5 The methods and systems to be described with reference to the drawings are concerned with monitoring physiological conditions, such as heart activity, respiration and body temperature, of a baby in the context of a home environment, during sleep. However, the methods and systems of the invention may be used in a more general
10 context than this; for example, the principles involved may be used for physiological monitoring of adults, whether at home or in hospital, during athletic or hazardous pursuits, and may also be used for monitoring animal subjects.

15 Referring to Figure 1, the baby wears a closely-fitting cotton vest 1 of conventional style. The vest 1, which is seamless and machine-knitted to the general shape of the baby's torso, has stretch both longitudinally and
20 laterally of the baby's body so that it hugs the upper part of the body closely from shoulders to hips. The bi-directional stretch and seamlessness are of especial advantage in retaining the vest closely against the body in the abdominal region without significant tenting, that
25 is to say, lifting up of the vest 1, over the baby's nappies or diapers.

A fabric patch 2 of decorative shaping and colouring (shown in Figure 1 with the design format of an owl) is
30 attached to the front of the vest 1. The patch 2, which is some 50 mm in width and some 100 mm in length, is of laminate construction and is attached to the vest 1 to bridge the baby's thoracic and abdominal regions. An electrical circuit is incorporated within the laminate of
35 the patch 2 for sensing manifestations of the baby's vital signs in these regions and transmitting

electromagnetic-wave signals in accordance therewith for reception and monitoring remotely of the baby.

5 The construction of the patch 2 is illustrated in Figures 2 and 3, and will now be described. The patch 2 is shown in Figure 2 for ease of representation, as though having a rectangular configuration rather than the owl-shaping of Figure 1.

10 Referring to Figures 2 and 3, the electrical circuitry of the patch 2 includes a printed-circuit board 3 carried by a flexible substrate 4. The substrate 4 and the board 3 are cushioned from impact-damage by a covering layer 5 of
15 foamed-plastics material, and the substrate 4 with its covering layer 5 are sandwiched between two flexible waterproof-sheets 6 and 7 that are bonded to the layer 5 and substrate 4 respectively. The sheets 6 and 7 are bonded together around their peripheries so as to encapsulate the substrate 4 and the board 3. A top,
20 outer layer 8 of the patch 2 is bonded to the sheet 6, and the sheet 7 is bonded to a backing sheet 9 by which the patch 2 is attached to the vest 1.

25 The layer 8 is of a fabric that carries the decorative design (an owl in Figure 1), and whereas the backing sheet 9 may be fastened to the vest 1 by means of press-stud, laced or button fixing, it is preferably, as illustrated, secured by fabric fastening based on fibre hook-and-eye inter-engagement (such as sold under the
30 Registered Trade mark VELCRO). More particularly, the sheet 9 is of a stretchable fabric having its exposed, back surface formed with upstanding fibres of hook configuration that engage with the fibres of the vest-material to secure the sheet 9, and with it the circuitry
35 of the substrate 4, to the vest 1 firmly but releasably.

The appropriate location on the vest 1 for attachment of the patch 2 may, if desired, be delineated by lines or other markings printed or otherwise incorporated in the vest 1. Because of the fabric fastening, the patch 2 is very easily attached merely by laying it in place and applying gentle pressure to consolidate the hook-fibre engagement of the backing 9 with the vest 1; removal is carried out simply by gripping the patch 2 by hand and stripping it away. The attachment of the patch 2 anchors the substrate 4 to the vest 1 so that it is subject to strain in accordance with the elastic extensions and contractions of the vest-material as the baby breathes in and out. These deflections of the vest are sensed by two parallel strips 10 and 11 of piezo-electric film that are bonded in face-to-face contact with the substrate 4 to sense bending and/or stretching. The strips 10 and 11 are spaced from one another longitudinally of the patch 2 (normally, by more than 50 mm) to function as strain gauges for the thoracic and abdominal regions of the baby's body, within the electrical circuitry carried within the patch 2.

The electrical circuitry of the patch 2 is shown schematically in Figure 4, and, as shown in Figure 4, the signals supplied from electrodes 12 of the film strips 10 and 11 are passed via respective pre-amplifiers 13 to a microprocessor 14. The pre-amplifiers 13 and the microprocessor 14 form part of a signal-processing chip 15 that, together with a controller 16, is mounted on the printed-circuit board 3 of the substrate 4. The microprocessor 14 is controlled by the controller 16 to derive health-related data in accordance with the output signals of the pre-amplifiers 13 and a signal dependent on the baby's body-temperature supplied from a thermistor 17 (not shown in Figure 2).

The health-related data derived by the microprocessor 14 is supplied to a signal-transmitter 18 of the chip 15, for low-power electromagnetic-wave transmission from an inductive-loop antenna 19 to a remote receiver. The loop antenna 19 is printed on the substrate 4 to encircle the board 3 and the strips 10 and 11. The board 3 carries a re-chargeable battery 20 for powering the patch 2, and the whole of the circuitry within the loop-antenna 19 is protected from external electrical interference by screening on the sheets 6 and 7.

The location of the patch 2 on the vest 1 is such as to place the film-strips 10 and 11 extending laterally of the baby's thorax and abdomen respectively, so that the signals generated by the strips 10 and 11 are dependent on the respiratory movements in those respective regions; the strips 10 and 11 also respond to the baby's heart beat as conveyed via the rib cage and abdomen respectively. Moreover, the signals generated by the strips 10 and 11 include components that are dependent generally on the hydraulics of the baby's heart, and respiratory sounds, in particular, wheezing. These signals are filtered within the pre-amplifiers 13 to remove unwanted noise before being passed to the microprocessor 14 along with the temperature signal from the thermistor 17.

The thermistor 17, which is of miniature bead form, is preferably located on the substrate 4 in the region of the abdomen, over the baby's liver. It has been found that it is not necessary for the thermistor 17 to be in direct contact with the baby's skin for substantially accurate monitoring of body temperature, and changes in temperature, to be facilitated.

The signals supplied from the pre-amplifiers 13 and the thermistor 17 are processed within the microprocessor 14

to derive digital data in accordance, principally, with thoracic-related activity, abdomen-related activity and body temperature. The data is derived according to a program involving sampling and frequency analysis of the input signals and using data-compression techniques, and is supplied for transmission by the transmitter 18. The transmitter 18 is operable to transmit the data via the antenna 19 in periodic bursts, but this operation can be overridden to provide for continuous transmission when required.

The transmission from the antenna 19 is received at a station remote from the baby, for example, in a unit attached to the outside of the baby's cot or located elsewhere in the same or another room. A unit suitable for use at the remote station is illustrated schematically in Figure 5 and will now be described.

Referring to Figure 5, a receiver unit 21 for location remotely of the baby includes an antenna 22 for receiving the data transmissions from the patch 2. The received data is supplied from the antenna 22 to a microprocessor 23 and is there submitted to adaptive filtering and other techniques for deriving signal representations dependent upon the baby's vital signs. These representations are written to a RAM section of memory 24 of the unit 21 for storage, and are continuously monitored within the microprocessor 23 for response to incipient conditions affecting the baby's welfare. More particularly in the latter respect, the representations are monitored by the microprocessor 23 against clinical criteria stored in a ROM section of the memory 24, and the unit 21 includes an alarm 25 that is triggered from the microprocessor 23 to provide both an audible and a visual warning signal whenever this is warranted. A digital display device 26 is also included for displaying values in accordance with

whichever of the derived representations is selected using a selector device 27 of the unit 21.

The unit 21, which is powered by a re-chargeable battery 28, may (as shown in Figure 5) also include, selectively, a VHF transmitter capsule 29. The transmitter capsule 29 is adapted to be inserted into the unit 21 and when so inserted converts the unit 21 to transmit information about the baby's physiological condition by VHF radio signals to a radio-receiver located at a distance and, for example, carried by a parent or nurse. Use of the capsule 29 in the unit 21 enables long-range communication to be achieved without locating a high-power transmitter on the baby.

One of the representations derived within the unit 21 and written to the RAM section of the memory 24, is that of the degree of the synchrony/asynchrony between the thoracic and abdominal respiratory motions of the baby. The microprocessor 23 acts in this to determine the relative phasing of the signals in accordance with the frequency and depth of breathing monitored by the piezo-electric strips 10 and 11. However, representations of the rate and tidal volume of respiration are also derived from these signals, and any components of them that are indicative of deterioration in respiration caused by wheezing or restriction of the baby's airway, are recorded. Furthermore, representations of pulse frequency and rhythm are derived together with representations of temperature and change of temperature, in accordance with the signals received from the patch 2.

A portable data logger 31 is connectable to the unit 21 to access the data stored in the RAM section of the memory 24. The data logger 31 includes, in addition to a processor 32, a digital-audio tape store 33 for receiving and retaining data from the memory 24 and storing it over

a long period for detailed analysis. It may also include, as shown, a plotter 34 for providing a graphical display of the information accumulated, a key-pad 35 for entering data and making selections, and a modem 36 for
5 down-loading data for computer analysis.

Data is normally transmitted from the transmitter 18 of the patch 2 in periodic bursts in order to conserve battery power. However, as indicated above, it is
10 possible to override this operation of the transmitter 18 to provide continuous transmission. This is achieved by means of a magnetically-operated switch (not shown) incorporated in the circuitry of the patch 2 and connected to the transmitter 18. The setting of the
15 switch determines whether the transmission is periodic or continuous and is changed simply by passing a magnet in one or the other direction over the patch 2. The switch may also be connected to the pre-amplifiers 13 so that when set for continuous transmission, the signal-
20 filtering function carried out within the pre-amplifiers 13 is by-passed.

The sensing within the patch 2 of thoracic and abdominal movements, may be carried out using techniques other than
25 the piezo-electric sensing involved in the film strips 10 and 11; for example, sensing based on the Hall effect, may be used. However, the use of piezo-electric film may be extended in that a single sheet of the film may replace the discrete strips 10 and 11, this film when
30 printed with appropriately-conductive ink, not only providing the strain-gauge sensors required in the thoracic and abdominal regions (and possibly elsewhere too) but acting as the substrate for all the circuitry of the patch 2 in place of the substrate 4. The film in
35 this latter case, as well as in the discrete-strip form, may be configured to respond to bending, perhaps to a greater extent than stretch; the response can be modified

in this respect where the film is in the form of a double-film laminate, by varying the relative orientations with which the laminations are bonded together face to face.

5

The patch 2 is removable from the vest 1 to enable the vest 1 to be laundered without the possibility of damage to the electrical circuitry, and to enable easy replacement when the charge of the battery 20 is exhausted and in the event of circuit fault. However, the patch 2 may be attached to the vest 1 permanently if desired, and in either case, may be attached inside the vest 1 rather than on the outside. As an alternative, it may be accommodated under a flap or within a pocket of the vest, so as not only to locate it precisely, but at least partially to conceal it and to limit the possibility of it being detached by the baby. A health-monitoring system involving a vest with a flap or pocket to accommodate a patch in this way, is illustrated in Figure 6, and will now be described.

20

Referring to Figure 6, the vest 41 in this case has the same general stretch qualities as the vest 1 of Figure 1, but the patch 42 used is inserted under a flap 43 that covers a partial opening 44 in the front. The opening 44 contributes to the stretch available in the vest 41 where sensing is to occur, and the patch 42 (which is essentially the same as the patch 2 described above) is inserted under the flap 43 bridging the opening 44. The patch 42 is attached by fabric hook-and-eye fastening to the margin of the vest 41 around the opening 44, and the flap 43 is closed over it; the flap 43 is held there, also by fabric hook-and-eye fastening to the vest 41 and, possibly, to the patch 42 too.

35

A small window 45 (in the form an aperture or a thinned portion) in the flap 43 is provided to reveal artwork 46

of the patch 42 and confirm its location on the vest 41.
In the illustrated embodiment, the artwork 46 depicts a
spaceman and the window 45 is located on the flap 43
within artwork 47 that depicts a spaceship, so that the
5 head of the spaceman appears at the spaceship window 45
when the patch 42 is correctly in place.

Claims:

1. A method for monitoring vital signs of a human or animal subject, wherein the subject wears a vest in the form of a garment that has stretch both laterally and longitudinally of the subject's body to fit the body closely, elastic deflections of the vest related to respiratory and/or heart functions of the subject are sensed in both the thoracic and abdominal regions of the subject by sensors that are carried by a common carrier attached to the vest, and signals dependent on the sensed deflections are transmitted for reception and analysis remotely of the subject.
2. A method according to Claim 1 wherein the sensors comprise piezo-electric sensors that are located on the common carrier to lie respectively within the thoracic and abdominal regions of the subject.
3. A method according to Claim 1 or Claim 2 wherein the subject's body temperature is sensed by sensing means carried by the common carrier, and the transmitted signals include a signal dependent on the sensed temperature.
4. A method according to any one of Claims 1 to 3 wherein the signal transmission is by electromagnetic-wave transmission from the common carrier.
5. A method according to any one of Claims 1 to 4 wherein the transmitted signals received remotely are processed to provide representation dependent on thoracic-abdominal motion synchrony/asynchrony.
6. A method according to any one Claims 1 to 5 used for apnoea-monitoring of a baby.

7. A system for monitoring vital signs of a human or animal subject, comprising a vest for wear by the subject in the form of a garment that has stretch both laterally and longitudinally of the subject's body to fit the body closely, sensors that are carried by a common carrier attached to the vest, for sensing in both the thoracic and abdominal regions of the subject elastic deflections of the vest related to the subject's respiratory and/or heart functions, and means for transmitting signals dependent on the sensed deflections for reception and analysis remotely of the subject.

8. A system according to Claim 7 wherein the sensors comprise two piezo-electric sensors that are located on the common carrier for responding to the elastic deflections of the vest in the thoracic and abdominal regions respectively.

9. A system according to Claim 7 or Claim 8 including temperature-sensing means carried by the common carrier for responding to the subject's body temperature, and wherein the signals transmitted by the transmitting means include a signal dependent on the response of the temperature-sensing means.

10. A system according to any one of Claims 7 to 9 wherein the common carrier is attached to the vest to bridge the subject's thoracic and abdominal regions.

11. A system according to any one of Claims 7 to 10 wherein the common carrier is a patch that is removably attached to the vest.

12. A system according to Claim 11 wherein the patch is attached to the vest by a fabric fastening involving the inter-engagement of hook fibres with fibres of the vest.

13. A system according to Claim 11 wherein the patch is attached to the vest under a flap or within a pocket of the vest.

14. A system according to any one of Claims 11 to 13 wherein the patch is of laminate form having a fabric top layer.

15. A system according to any one of Claims 7 to 14 wherein the transmission means is means for electromagnetic-wave transmission of the signals dependent on the sensed deflections.

16. A system according to Claim 15 wherein the transmission means is carried by the common carrier.

1/4




Fig. 1

2/4





Fig. 3

3/4

Fig. 4





Fig. 5

4/4




Fig. 6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/GB 92/02064

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC Int.Cl. 5 A61B5/113; A61B5/00		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
Int.Cl. 5	A61B	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in the Fields Searched ⁸		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category ¹⁰	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
X	WO,A,8 802 237 (ADVANCED MEDICAL TECHNOLOGIES, INC.) 7 April 1988 see page 5, line 1 - page 7, line 34 see page 11, line 25 - page 12, line 15 ---	1,4,5,7 8,10,12 15,16
X	GB,A,2 116 725 (THE SECRETARY OF STATE FOR SCOTLAND) 28 September 1983 see page 2, line 13 - line 101 see page 3, line 14 - line 46 ---	14-8,10 12,15
A	US,A,4 245 651 (J.K. FROST) 20 January 1981 see column 2, line 3 - line 68 ---	1,6,7,11 11,13
A	DE,A,3 444 635 (HUGO SACHS ELEKTRONIK) 19 June 1986 see page 7, line 1 - page 8, column 27 ---	1,2,5-8
-/--		
¹⁰ Special categories of cited documents: "A" document defining the general state of the art which is not considered to be of particular relevance "E" earlier document but published on or after the international filing date "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) "O" document referring to an oral disclosure, use, exhibition or other means "P" document published prior to the international filing date but later than the priority date claimed "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art. "&" document member of the same patent family		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search 01 MARCH 1993		Date of Mailing of this International Search Report 25. 03. 93
International Searching Authority EUROPEAN PATENT OFFICE		Signature of Authorized Officer RIEB K.D.

III. DOCUMENTS CONSIDERED TO BE RELEVANT (CONTINUED FROM THE SECOND SHEET)		
Category *	Citation of Document, with indication, where appropriate, of the relevant passages	Relevant to Claim No.
A	DE,A,1 908 652 (LICENTIA) 3 September 1970 see page 4, line 11 - page 8, line 11 ---	1,3,4,7 9,15,16
A	US,A,4 471 354 (R.B. SMITH) 11 September 1984 see column 3, line 22 - line 53 -----	1,3,4,7 9,12,13, 15

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.**

GB 9202064
SA 67077

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information. 01/03/93

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-8802237	07-04-88	US-A- 4784162 US-A- 4827943	15-11-88 09-05-89
GB-A-2116725	28-09-83	None	
US-A-4245651	20-01-81	None	
DE-A-3444635	19-06-86	None	
DE-A-1908652	03-09-70	None	
US-A-4471354	11-09-84	None	

EPO FORM P0479

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

